

ATLANTIC SAND / SCREED PUMP - Diesel Hydraulic Models



Atlantic Sand/Screed Pump ASP 5000 is a well-designed and user-friendly pneumatic conveyor. It is simple to operate, easy to service and offers productivity of 5 m³/hr. Equipped with an in-built air compressor and a large vessel outlet, the machine is ideal for mixing and conveying dune sand, floor screed, gravel and fine-grained concrete to higher floors and longer distances.

The German engineered diesel-hydraulic models come with a powerful Deutz diesel engine and a groundbreaking cooling system. The patented twin hydraulic-driven cooling fans are designed for Middle Eastern site conditions.

A stainless steel hood displays robust construction and quality workmanship. The machine features an automatic central lubrication system, a spacious work area for easy and quick maintenance and a fuel tank in steel construction, with filler neck positioned outside.

ASP 5000 - Key Features:

- ✓ Stainless steel hood.
- Integrated working light.
- Automatic 2 bar shutdown.
- Safety shutdown at the dome sieve.
- **I** Easy belt replacement of the mixer.
- Corrosion-resistant EPD coated frame.
- ✓ Lockable toolbox.
- **V** Rugged steel fenders.
- ✓ Powerful/reliable Deutz engine.





Safety Guard

Patented Cooling System



- ✓ Oil cooled screw compressor.
- ✓ Fuel tank in steel construction.
- ✓ Fuel filler neck positioned outside.
- Height adjusting coupling device.
- ✓ Mixing vessel with high-strength wear plates.
- Sturdy chassis with mechanical overrun brakes.
- \checkmark 1.9 ton or 2.5 ton axle as standard equipment.
- ✓ Noise level as per 2000/14/EG guidelines.





Adjustable Coupling

Easy Refueling

* Pneumatic Conveyor * Sand Transfer Machine * Floor Screed Equipment * Liquid Screed Pump * Mortar Pump * Fine Grained Concrete Pump *



BRIDGING THE GAP









Easy Belt Replacement

Twin Hydraulic Driven Cooling Fans

ATLANTIC SAND / SCREED PUMP - SPECIFICATIONS		
Models	ASP 5000 ^{4DHL}	ASP 5000 ^{4DHLS}
Machine Type	Pneumatic Conveyor with Hydraulic Loader	
Max. Output (Theor.) *	5 m ³ /hr	
Max. Delivery Pressure	8.5 bar	
Max. Conveying Distance *	150 m horizontal or 50 m vertical	
Air Compressor	5 m ³ /min	
Mixing Vessel	260 litre	
Filling Height	450 mm	
Loading Bucket Volume	310 litre	
Max. Grain Size	16 mm	
Fuel Tank Capacity	60 litre	
Prime Mover	Deutz 4 cylinder diesel engine 46 kW	
Weight	1900 kg	2150 kg
Dimensions (L x B x H)	4970 x 1560 x 2250 mm	4970 x 1560 x 2250 mm
* All data is based on experience and dependent on the materials used. Machine design and construction are subject to technical modifications and upgrades.		

ASP 5000 - Optional Features:

- Crane lifting eyes.
- ✓ Silo feeding system.
- Spray pistol for easy cleaning.
- Central/auto lubrication system.
- ✓ Long life mixer wear plates (8 mm thick).
- ✓ High-strength wear plates (10 mm thick).
- ✓ Large outlet of mixing vessel minimizes material blockage.
- **W** Hydraulic loading feeder bucket, for quick filling of the mixing vessel.
- **W** Hydraulic loading feeder bucket with radio remote controlled scraper winch.
- **W** Two galvanized filter cages for the cooling system, provided with a magnetic base and filter cap.

DELIVERING MORE EFFICIENCY, FLEXIBILITY AND POWER



ACE CENTRO ENTERPRISES

P. O. Box 95325, Abu Dhabi - U.A.E. T : +971 2 6737900 F : +971 2 6737800

E : salesteam@acecentro.com W : www.acecentro.com



